

Superior Chemistry. Superior Performance.



SYNTHETIC BLEND 20W-50 RACING OIL



Superior Chemistry. Superior Performance.



SYNTHETIC BLEND 20W-50 RACING OIL

MAG 1 Synthetic Blend Racing Oil is specially formulated to give excellent anti-wear, anti-oxidancy, anti-corrosively, sludge control, and TBN retention while helping you beat your competition. Benefits include:

- Reduced friction for excellent protection against engine wear under the most grueling conditions including racing
- High amounts of anti-wear ZDDP with high boundary protection for extreme shock load performance
- High cling on performance to minimize wear



For use in racing engines including those with flat tappet camshafts where an API specification 20W-50 motor oil is recommended. For off-road use only.

Typical Physical Properties of MAG 1 Synthetic Blend Racing Oil

Test	Method	Typical Results
Gravity, °API	ASTM D287	30.73
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8722
Viscosity @ 40°C cSt	ASTM D445	155
Viscosity @ 100°C cSt	ASTM D445	19
Viscosity Index	ASTM D2270	139
Cold Cranking Simulator at (°C), cP	ASTM D5293	5691 (-15)
Color	ASTM D 1500	2.5
Zinc, wt. %	ASTM D 5185	.126
Phosphorus, wt. %	ASTM D 5185	.11
Calcium, wt. %	ASTM D 5185	.297
Boron, wt. %	ASTM D 5185	.0318
Molybdenum, wt. %	ASTM D 5185	.0114

Pack Size	Stock # / Order #	Each UPC	Case UPC	Shipping UPC	Case Dimensions	Case Cube / Pallet Cube	Case Weight / Pallet Weight	Pallet Stack
6/1 Quart	62888 / MGR454PL	0 71621-62888 1	0 71621-62889 8	1 00 71621-62888 8	L 9.500 x W 7.625 x H 9.625	0.403 / 77.778	12.427 / 2087.813	168 Cases (7 layers of 24)

