



PROVEN PROTECTION FOR YOUR VEHICLE AND THE PLANET

Safety-Kleen Systems, Inc.
www.safety-kleen.com, www.ecopoweroil.com

NGP 15W-40 NATURAL GAS ENGINE OIL

EcoPower® NGP 15W-40 NATURAL GAS ENGINE OIL is specially formulated to satisfy the requirements of natural gas fueled heavy duty engines. It is formally approved for use in natural gas engines with OEM specification Cummins CES 20074.

EcoPower® Heavy Duty Engine Oils provide maximum protection for longer engine life. EcoPower's robust formulation includes:

- **Highest quality re-refined base oils** with exceptional purity and lubricating properties that heavy-duty applications demand.
- **State-of-the-art performance additives** including viscosity index improvers, detergents, dispersants, and anti-wear agents provide maximum protection against breakdown and engine wear
 - Unmatched varnish, sludge and carbon deposit control
 - Low valve train, ring and linear wear
 - Extra protection against bearing and bushing corrosion
 - Boosted oxidation control to minimize oil thickening
 - Excellent high-temperature stability
 - Controls oil thickening and provides good filterability with newer, high soot producing, emission-controlled engines
- **EcoPower Engine Oil is beneficial for the environment:**
 - Conserves valuable, non-renewable resources
 - Takes up to 85% less energy to produce than oils made from crude according to recent Dept. of Energy study
 - Reduces greenhouse gas emissions by over 80%

TYPICAL PROPERTIES		
ECOPOWER®	SAE	15W-40
Kinematic Viscosity		
cSt @ 40°C		104.5
cSt @ 100°C		14.5
Viscosity Index		143
CCS Viscosity		
cP @ -20°C		4900
Flash Point, °C		240
Pour Point, °C		-39
Color (ASTM)		L 3.0
Specific Gravity 15.6°C (60°F)		0.867
TBN		4.7
TAN		1.9
Sulfated Ash wt%		0.59

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 040913



Customer Service **800.669.5740**

Safety-Kleen Systems, Inc.
2600 N. Central Expressway, Suite 400, Richardson, TX 75080