



# Pioneer Premiere Synthetic Blend Passenger Car Motor Oils

## Applications

Pioneer Premiere Synthetic Blend Passenger Car Motor Oils are formulated for turbo-charged and naturally aspirated gasoline, propane, natural gas engines in passenger car and light duty truck service. They meet or exceed API SN and previous service categories and the requirements of ILSAC Starburst GF-5.

## Features

Pioneer Premiere Synthetic Blend Passenger Car Motor Oils maintain the warranty requirements for today's passenger car and light duty trucks.

Protects the engine in controlling varnish, deposits, rust, corrosion, wear and cleanliness while reducing high temperature oxidation.

Energy-Conserving for improved fuel economy.

Pioneer Premiere Synthetic Blend Passenger Car Motor Oils meet or exceed the following specifications:

API SN, SM and SL \* ILSAC GF-5 and GF-4

Chrysler MS-6395 \* GM 6094M \* M2C945-A and M2C930-A

Typical Specifications	5w-20	5w-30	10w-30
Specific Gravity @ 60°F	0.8601	0.8604	0.8717
Viscosity @ 40°C cSt	46.37	57.82	67.73
Viscosity @ 100°C cSt	8.154	10.02	10.29
Pour Point °C (°F)	-45 (-49)	-45 (-49)	-42 (-44)
Viscosity Index	150	161	138
CCS Viscosity at (°C), cP	(-30) 5962	(-30) 6202	(-25) 6249
High Temp / High Shear Vis at 100°C, cP	6.02	6.9	7.31
High Temp / High Shear Vis at 150°C, cP	2.79	3.2	3.14
Color	2.5	2.5	2.5
Gravity, °API	33.02	32.96	30.83

**PIONEER**  
D I S T R I B U T I N G C O .

**Quality Products \* Excellence In Service  
Since 1947**

1300 North 24th Avenue  
Phoenix, AZ 85009-3618

Phone: 602-278-2693  
Fax: 602-278-0285  
[www.pioneerdistributing.com](http://www.pioneerdistributing.com)