



Pioneer Premiere Tile Oil WOA

Applications

Pioneer Premiere Tile Oil WOA is recommended for lubricating steel or wood forms into which concrete is poured.

Features

Pioneer Premiere Tile Oil WOA is a mineral base lubricant for application on wood or steel forms used in concrete construction.

Oleic acids assure integrity of protective film during application by pressure spray; where preferred, material can be applied with brush or swab or by dipping.

Excellent lubricity and forms-covering power help minimize surface cavitation, thus reducing the need to patch voids in concrete surfaces.

Tough Lubricant film prevents forms from sticking to poured concrete, thus promoting a smooth concrete finish and easy removal of forms.

Light color minimizes discoloration of concrete.

Protective lubricant film eliminates cleaning of steel and wood forms for manpower savings.

Typical Specifications

Specific Gravity @ 60°F	0.849
Pour Point, °F, D97	0
Viscosity @ 100°F, D445	24.8
Flash Point, °F, D92	442
Color, D1500	L 0.5

PIONEER
D I S T R I B U T I N G C O .

Quality Products * Excellence In Service
Since 1947

1300 North 24th Avenue
Phoenix, AZ 85009-3618

Phone: 602-278-2693
Fax: 602-278-0285
www.pioneerdistributing.com