



Pioneer Premiere 3% Moly #2

Applications

Pioneer Premiere 3% Moly #2 Grease is recommended for wheel bearings, fifth wheel, U-Joints, steering linkage and chassis lubrication.

Recommended as a chassis lubricant in both on and off road equipment where severe water washing or shock loading protection is required.

Recommended for all type of bearings including plain bearings, heavily loaded journal bearings, ball and roller bearings, needle bearings and couplings.

Features

NLGI Service Classification GC-LB.

Formulated with 3% molybdenum disulfide to provide protection against sliding friction wear. Fully additive treated: antiwear, tackiness adhesives, rust, corrosion and oxidation inhibited. Water insoluble with superior water washout resistance and shock load-carrying ability.

Typical Specifications

NLGI Consistency Number	2
Thickener	Lithium Complex
Texture	Smooth, Adhesive
Color	Dark Grey
Worked Penetration @ 77°F	265-295
Dropping Point, °F	500
Timken OK Load, Minimum	70 lbs.
Base Oil Viscosity cSt @ 40°C	220
Base Oil Viscosity cSt @ 100°C	14.3
Water Washout Loss %	5

PIONEER
D I S T R I B U T I N G C O .

Quality Products * Excellence In Service
Since 1947

1300 North 24th Avenue
Phoenix, AZ 85009-3618

Phone: 602-278-2693
Fax: 602-278-0285
www.pioneerdistributing.com