



Pioneer Premiere Tractor Fluid

Applications

Pioneer Premiere Tractor Fluid is recommended for use in tractors and other farm implements having combination transmission, differential, wet brake and hydraulic equipment.

Features

Pioneer Premiere Tractor Fluid is manufactured from premium, high VI, paraffinic base stocks that are fortified with inhibitors to help prevent rusting, foaming, oxidation, chatter and wear. Other additives are used to protect rubber seals from excessive swelling or shrinking. Special friction modifiers are added to insure the proper operation of wet brakes and clutches.

Reduces wear in gears and bearings and stops excessive chatter and grabbing. Prevents sludge formation in control valves. Anti-wear protects pumps and gears. Low pour means good response at low temperatures. Friction modifier protects wet brakes and clutches.

Meets or exceeds the following qualifications:

Allison C-4, C-3, C-2 Fluid. - API THF Classification. - Caterpillar TO-2.
Massey-Fergusson M-1110, M-1127A and B, M-1129A (PermaTran III) and M-1135.
International Harvester B-6 (Hy-Tran). - Kubota UDT Hydraulic / Transmission Fluid.
Sundstrand Hydrostatic Transmission Fluid. - White Q-1826, 1766B, 1766, 1722, 1705.
J.I. Case - TCH Oil, TFD Fluid, JIC 143, 144, 145, 185, MS 1204, 1205, 1206, 1207, 1210.
John Deere JDT 303, Hy-Gard, J14B, J14C, J20A/B/C and J21A. - Ford New Holland ESN-M2C134-D

Typical Specifications

Specific Gravity @ 60°F	0.8629
Viscosity @ 40°C cSt	60.89
Viscosity @ 100°C cSt	9.53
Viscosity Index	139
Pour Point °C (°F)	-42 (-44)
Brookfield Viscosity at -35°C, cP	37,500
Gravity, °API	32.48

PIONEER
D I S T R I B U T I N G C O .

Quality Products * Excellence In Service
Since 1947

1300 North 24th Avenue
Phoenix, AZ 85009-3618

Phone: 602-278-2693
Fax: 602-278-0285
www.pioneerdistributing.com